

# Resistance Thermometer for screwing in

Form 2G acc. to DIN 43772-2  
also with exit 4...20 mA



## Description

Form 2 G-Resistance thermometers are used as universal thermometers preferably in processes with liquid and gas media under low pressure.

The standard head is type B according to DIN 43 763. On request other types as type BUZ (for build in of head transmitters), type BBK (plastic head) or type BUSH (for build in of intrinsically safe head transmitters) can be used.

The listed thermowells can be used for pressures up to 36 bar, depending on the process conditions. Different materials or overlays are available for mechanical or chemical protection. Beneath the extension tube is a fixed screw G1/2 A, G3/4 A or G 1 A for connecting the thermometer on the process. Other connectings are available.

A standard sensor PT 100/2-wire, class B-type according to DIN IEC 751 is build in. On request 3- or 4-wire or double elements with 2- or 3-wire connection can be used.

## Features

- Universal thermometer for low
- Interchangeable insert according DIN
- Great choice of standard versions
- Special versions on request

## Measuring range

-200 ... +600 °C

## Applications

Air conditioning  
Tank and pipe constructions  
chemical industry  
Machinery, heating and oven construction

Technical data: RTD's for screwing in

Type	7010, 7020		Options
Design			
Description	Form 2G acc. to DIN 43772-2		
Process Connection	G 1/2 A, G 3/4 A		G 1 A
Thermowell			
Diameter	Ø 9 mm Ø 11 mm		Ø 11 mm Ø 14 mm
Stem length L <sub>1</sub>	160 mm 250 mm 400 mm		160 mm 250 mm 400 mm
Materials	1.4571		1.4541 1.7335
Extension tube	145 mm		
Connection head	Form B acc. to DIN 43729 Waterproof IP 54 acc. to DIN 40050 Immersion tube connection M 24 x 1,5 <b>Although available:</b> Plain stem 15,5 mm, or with screw G 1/2 A		Form BUZ Form BUS Form BUZH Form BUSH
Sensor element	1x PT 100/2-wire Standard 1x PT 100/3-wire 1x PT 100/4-wire 2x PT 100/2-wire 2x PT 100/3-wire acc. to DIN 751, class B		class A

Modifications reserved!